



MECHANICS OF SOLIDS

Jiří Plešek

Institute of Thermomechanics
Czech Academy of Sciences



Contents

- Lagrange description
- Constitutive equations
- Thermoelasticity
 - Fourier 'law'
- Example: Uniaxial stress
 - Spurious buckling modes



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$

2. $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$

2. $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$

3. $\boldsymbol{\sigma} \text{ sym} \Rightarrow \mathbf{P}\mathbf{F}^T = \mathbf{F}\mathbf{P}^T$



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$

2. $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$

3. $\boldsymbol{\sigma} \text{ sym} \Rightarrow \mathbf{P}\mathbf{F}^T = \mathbf{F}\mathbf{P}^T$

4. $\mathcal{K} - \text{Div } \mathbf{H} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} = \rho_0 \dot{u}$



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$

2. $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$

3. $\boldsymbol{\sigma} \text{ sym} \Rightarrow \mathbf{P}\mathbf{F}^T = \mathbf{F}\mathbf{P}^T$

4. $\mathcal{K} - \text{Div } \mathbf{H} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} = \rho_0 \dot{u}$

5. $-\rho_0 \eta \dot{T} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} - \frac{1}{T} \mathbf{H} : \text{Grad } T \geq \rho_0 \dot{\psi}$



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$ (checked)

2. $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$

3. $\boldsymbol{\sigma} \text{ sym} \Rightarrow \mathbf{P}\mathbf{F}^T = \mathbf{F}\mathbf{P}^T$

4. $\mathcal{K} - \text{Div } \mathbf{H} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} = \rho_0 \dot{u}$

5. $-\rho_0 \eta \dot{T} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} - \frac{1}{T} \mathbf{H} \cdot \text{Grad } T \geq \rho_0 \dot{\psi}$



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$ (checked)

② $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$

3. $\boldsymbol{\sigma} \text{ sym} \Rightarrow \mathbf{P}\mathbf{F}^T = \mathbf{F}\mathbf{P}^T$

4. $\mathcal{K} - \text{Div } \mathbf{H} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} = \rho_0 \dot{u}$

5. $-\rho_0 \eta \dot{T} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} - \frac{1}{T} \mathbf{H} \cdot \text{Grad } T \geq \rho_0 \dot{\psi}$



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$ (checked)

② $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$

3. $\boldsymbol{\sigma} \text{ sym} \Rightarrow \mathbf{P}\mathbf{F}^T = \mathbf{F}\mathbf{P}^T$ (const. eqns.)

4. $\mathcal{K} - \text{Div } \mathbf{H} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} = \rho_0 \dot{u}$

5. $-\rho_0 \eta \dot{T} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} - \frac{1}{T} \mathbf{H} : \text{Grad } T \geq \rho_0 \dot{\psi}$



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$ (checked)

② $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$

3. $\boldsymbol{\sigma} \text{ sym} \Rightarrow \mathbf{P}\mathbf{F}^T = \mathbf{F}\mathbf{P}^T$ (const. eqns.)

④ $\mathcal{K} - \text{Div } \mathbf{H} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} = \rho_0 \dot{u}$

5. $-\rho_0 \eta \dot{T} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} - \frac{1}{T} \mathbf{H} \cdot \text{Grad } T \geq \rho_0 \dot{\psi}$



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$ (checked)

② $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$

3. $\boldsymbol{\sigma} \text{ sym} \Rightarrow \mathbf{P}\mathbf{F}^T = \mathbf{F}\mathbf{P}^T$ (const. eqns.)

④ $\mathcal{K} - \text{Div } \mathbf{H} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} = \rho_0 \dot{u}$

5. $-\rho_0 \eta \dot{T} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} - \frac{1}{T} \mathbf{H} \cdot \text{Grad } T \geq \rho_0 \dot{\psi}$ (const. eqns.)



Lagrange description

Five conditions to meet:

1. $J\rho = \rho_0$ (checked)

② $\text{Div } \mathbf{P} + \mathbf{B} = \rho_0 \ddot{\mathbf{u}}$

3. $\boldsymbol{\sigma} \text{ sym} \Rightarrow \mathbf{P}\mathbf{F}^T = \mathbf{F}\mathbf{P}^T$ (const. eqns.)

④ $\mathcal{K} - \text{Div } \mathbf{H} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} = \rho_0 \dot{u}$

5. $-\rho_0 \eta \dot{T} + \boldsymbol{\Sigma} : \dot{\mathbf{E}} - \frac{1}{T} \mathbf{H} \cdot \text{Grad } T \geq \rho_0 \dot{\psi}$ (const. eqns.)

Four equations to solve: u_1, u_2, u_3, T .



Constitutive equations

Kinematics

$$\mathbf{u} \mapsto \mathbf{z}, \mathbf{F}, J \mapsto \mathbf{U}, \mathbf{E}$$



Constitutive equations

Kinematics

$$\mathbf{u} \mapsto \mathbf{z}, \mathbf{F}, J \mapsto \mathbf{U}, \mathbf{E}$$

Constitutive equations satisfying 3. and 5.



Constitutive equations

Kinematics

$$\mathbf{u} \mapsto \mathbf{z}, \mathbf{F}, J \mapsto \mathbf{U}, \mathbf{E}$$

Constitutive equations satisfying 3. and 5.

history: $0 \leq \tau \leq t$



Constitutive equations

Kinematics

$$\mathbf{u} \mapsto \mathbf{z}, \mathbf{F}, J \mapsto \mathbf{U}, \mathbf{E}$$

Constitutive equations satisfying 3. and 5.

history: $0 \leq \tau \leq t$

input $\mathbf{E}(\mathbf{X}, \tau)$, $T(\mathbf{X}, \tau)$ and compute



Constitutive equations

Kinematics

$$\mathbf{u} \mapsto \mathbf{z}, \mathbf{F}, J \mapsto \mathbf{U}, \mathbf{E}$$

Constitutive equations satisfying 3. and 5.

history: $0 \leq \tau \leq t$

input $\mathbf{E}(\mathbf{X}, \tau)$, $T(\mathbf{X}, \tau)$ and compute

- $\Sigma(\mathbf{X}, t) \mapsto \mathbf{P}, \boldsymbol{\sigma}$
- $\mathbf{H}(\mathbf{X}, t) \mapsto \mathbf{h}$
- $\psi(\mathbf{X}, t) \mapsto \eta, u$

Remark: In general, functionals must be formed.



Thermoelasticity

Assumption

$$\exists \psi(\mathbf{E}, T) : \quad \dot{\psi} = \frac{\partial \psi}{\partial E_{ij}} \dot{E}_{ij} + \frac{\partial \psi}{\partial T} \dot{T}$$



Thermoelasticity

Assumption

$$\exists \psi(\mathbf{E}, T) : \quad \dot{\psi} = \frac{\partial \psi}{\partial E_{ij}} \dot{E}_{ij} + \frac{\partial \psi}{\partial T} \dot{T}$$

Dissipation inequality

$$-\rho_0 \left(\eta + \frac{\partial \psi}{\partial T} \right) \dot{T} + \left(\Sigma_{ij} - \rho_0 \frac{\partial \psi}{\partial E_{ij}} \right) \dot{E}_{ij} - \frac{1}{T} \mathbf{H} \cdot \text{Grad } T \geq 0$$



Thermoelasticity

Assumption

$$\exists \psi(\mathbf{E}, T) : \quad \dot{\psi} = \frac{\partial \psi}{\partial E_{ij}} \dot{E}_{ij} + \frac{\partial \psi}{\partial T} \dot{T}$$

Dissipation inequality

$$-\rho_0 \left(\eta + \frac{\partial \psi}{\partial T} \right) \dot{T} + \left(\Sigma_{ij} - \rho_0 \frac{\partial \psi}{\partial E_{ij}} \right) \dot{E}_{ij} - \frac{1}{T} \mathbf{H} \cdot \text{Grad } T \geq 0$$

$$\eta = -\frac{\partial \psi}{\partial T} \quad \text{and} \quad \Sigma_{ij} = \rho_0 \frac{\partial \psi}{\partial E_{ij}}$$

Caution: Conjugate stress Σ respective to \mathbf{E} leaves the CE on output.



Fourier inequality

Reference configuration

$$\mathbf{H} \cdot \text{Grad } T \leq 0$$



Fourier inequality

Reference configuration

$$\mathbf{H} \cdot \text{Grad } T \leq 0$$

It follows that

$$\mathbf{H} = \text{function}(\text{Grad } T)$$



Fourier inequality

Reference configuration

$$\mathbf{H} \cdot \text{Grad } T \leq 0$$

It follows that

$$\mathbf{H} = \text{function}(\text{Grad } T)$$

$$H_i \frac{\partial T}{\partial X_i} = (J F_{ik}^{-1} h_k) \frac{\partial T}{\partial x_j} \frac{\partial x_j}{\partial X_i}$$



Fourier inequality

Reference configuration

$$\mathbf{H} \cdot \text{Grad } T \leq 0$$

It follows that

$$\mathbf{H} = \text{function}(\text{Grad } T)$$

$$H_i \frac{\partial T}{\partial X_i} = (J F_{ik}^{-1} h_k) \frac{\partial T}{\partial x_j} \frac{\partial x_j}{\partial X_i} = J F_{ji} F_{ik}^{-1} h_k \frac{\partial T}{\partial x_j}$$



Fourier inequality

Reference configuration

$$\mathbf{H} \cdot \text{Grad } T \leq 0$$

It follows that

$$\mathbf{H} = \text{function}(\text{Grad } T)$$

$$H_i \frac{\partial T}{\partial X_i} = (J F_{ik}^{-1} h_k) \frac{\partial T}{\partial x_j} \frac{\partial x_j}{\partial X_i} = J \underbrace{F_{ji} F_{ik}^{-1}}_{\delta_{jk}} h_k \frac{\partial T}{\partial x_j}$$



Fourier inequality

Reference configuration

$$\mathbf{H} \cdot \text{Grad } T \leq 0$$

It follows that

$$\mathbf{H} = \text{function}(\text{Grad } T)$$

$$H_i \frac{\partial T}{\partial X_i} = (J F_{ik}^{-1} h_k) \frac{\partial T}{\partial x_j} \frac{\partial x_j}{\partial X_i} = J \underbrace{F_{ji} F_{ik}^{-1}}_{\delta_{jk}} h_k \frac{\partial T}{\partial x_j} = J h_k \frac{\partial T}{\partial x_k} = J \mathbf{h} \cdot \text{grad } T$$



Fourier inequality

Reference configuration

$$\mathbf{H} \cdot \text{Grad } T \leq 0$$

It follows that

$$\mathbf{H} = \text{function}(\text{Grad } T)$$


$$H_i \frac{\partial T}{\partial X_i} = (J F_{ik}^{-1} h_k) \frac{\partial T}{\partial x_j} \frac{\partial x_j}{\partial X_i} = J \underbrace{F_{ji} F_{ik}^{-1}}_{\delta_{jk}} h_k \frac{\partial T}{\partial x_j} = J h_k \frac{\partial T}{\partial x_k} = J \mathbf{h} \cdot \text{grad } T$$

Current configuration

$$\mathbf{h} \cdot \text{grad } T \leq 0$$




Fourier's 'law'





Fourier's 'law'




isotropy:

$$\mathbf{h} = -\lambda \text{grad } T$$

$$\lambda > 0 \text{ [W/mK]}$$



Fourier's 'law'



isotropy:


$$\mathbf{h} = -\lambda \text{grad } T$$

$$\lambda > 0 \text{ [W/mK]}$$

anisotropy:

$$[\lambda] \text{ (} 3 \times 3 \text{) sym+def}$$

Fourier's 'law'



isotropy:

$$\mathbf{h} = -\lambda \text{grad } T$$


$$\lambda > 0 \text{ [W/mK]}$$

anisotropy:

$$[\lambda] \text{ (} 3 \times 3 \text{) sym+def}$$

- In fact, Fourier's 'law' is merely a linear model.

Fourier's 'law'



isotropy:

$$\mathbf{h} = -\lambda \text{grad } T$$


$$\lambda > 0 \text{ [W/mK]}$$

anisotropy:

$$[\lambda] \text{ (} 3 \times 3 \text{) sym+def}$$

- In fact, Fourier's 'law' is merely a linear model.
- It violates the causality principle (parabolic vs. hyperbolic equation).

Fourier's 'law'



isotropy:

$$\mathbf{h} = -\lambda \text{grad } T$$

$$\lambda > 0 \text{ [W/mK]}$$

anisotropy:

$$[\lambda] \text{ (} 3 \times 3 \text{) sym+def}$$

- In fact, Fourier's 'law' is merely a linear model.
- It violates the causality principle (parabolic vs. hyperbolic equation).
- Good for small gradients or steady state solutions.



Example 5: Uniaxial stress (1/4)



$$\lambda = l/l_0 \quad \text{axial stretch}$$

$$\lambda_r = r/r_0 \quad \text{radial stretch}$$



Example 5: Uniaxial stress (1/4)



$$\lambda = l/l_0 \quad \text{axial stretch}$$

$$\lambda_r = r/r_0 \quad \text{radial stretch}$$

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix}$$



Example 5: Uniaxial stress (1/4)



$\lambda = l/l_0$ axial stretch

$\lambda_r = r/r_0$ radial stretch

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad J = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2$$



Example 5: Uniaxial stress (1/4)



$$\lambda = l/l_0 \quad \text{axial stretch}$$

$$\lambda_r = r/r_0 \quad \text{radial stretch}$$

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad J = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2 = \lambda \frac{A}{A_0}$$



Example 5: Uniaxial stress (1/4)



$\lambda = l/l_0$ axial stretch

$\lambda_r = r/r_0$ radial stretch

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad J = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2 = \lambda \frac{A}{A_0} = \frac{l}{l_0} \frac{A}{A_0} = \frac{V}{V_0}$$



Example 5: Uniaxial stress (1/4)



$$\lambda = l/l_0 \quad \text{axial stretch}$$

$$\lambda_r = r/r_0 \quad \text{radial stretch}$$

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad \underline{J} = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2 = \lambda \frac{A}{A_0} = \frac{l}{l_0} \frac{A}{A_0} = \frac{V}{V_0}$$

Example 5: Uniaxial stress (1/4)



$\lambda = l/l_0$ axial stretch

$\lambda_r = r/r_0$ radial stretch

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad \underline{J} = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2 = \lambda \frac{A}{A_0} = \frac{l}{l_0} \frac{A}{A_0} = \frac{V}{V_0}$$

$$[\sigma] = \text{diag} \left[\frac{F}{A} \ 0 \ 0 \right] \mapsto [P] = J[\sigma][F]^{-T}$$

Example 5: Uniaxial stress (1/4)


 $\lambda = l/l_0$ axial stretch

 $\lambda_r = r/r_0$ radial stretch

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad \underline{J} = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2 = \lambda \frac{A}{A_0} = \frac{l}{l_0} \frac{A}{A_0} = \frac{V}{V_0}$$

$$[\sigma] = \text{diag} \left[\frac{F}{A} \ 0 \ 0 \right] \mapsto [P] = J[\sigma][F]^{-T} = \lambda \frac{A}{A_0} \text{diag} \left[\frac{F}{A\lambda} \ 0 \ 0 \right]$$

Example 5: Uniaxial stress (1/4)


 $\lambda = l/l_0$ axial stretch

 $\lambda_r = r/r_0$ radial stretch

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad \underline{J} = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2 = \lambda \frac{A}{A_0} = \frac{l}{l_0} \frac{A}{A_0} = \frac{V}{V_0}$$

$$[\sigma] = \text{diag}\left[\frac{F}{A} \ 0 \ 0\right] \mapsto [P] = J[\sigma][F]^{-T} = \lambda \frac{A}{A_0} \text{diag}\left[\frac{F}{A\lambda} \ 0 \ 0\right] = \text{diag}\left[\frac{F}{A_0} \ 0 \ 0\right]$$

Example 5: Uniaxial stress (1/4)


 $\lambda = l/l_0$ axial stretch

 $\lambda_r = r/r_0$ radial stretch

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad \underline{J} = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2 = \lambda \frac{A}{A_0} = \frac{l}{l_0} \frac{A}{A_0} = \frac{V}{V_0}$$

$$[\sigma] = \text{diag}\left[\frac{F}{A} \ 0 \ 0\right] \mapsto [P] = J[\sigma][F]^{-T} = \lambda \frac{A}{A_0} \text{diag}\left[\frac{F}{A\lambda} \ 0 \ 0\right] = \text{diag}\left[\frac{F}{A_0} \ 0 \ 0\right]$$

$$\text{2nd-PK: } [S] = [F]^{-1}[P] = \text{diag}\left[\frac{F}{\lambda A_0} \ 0 \ 0\right]$$



Example 5: Uniaxial stress (1/4)

 $\lambda = l/l_0$ axial stretch $\lambda_r = r/r_0$ radial stretch

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad \underline{J} = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2 = \lambda \frac{A}{A_0} = \frac{l}{l_0} \frac{A}{A_0} = \frac{V}{V_0}$$

$$[\sigma] = \text{diag}\left[\frac{F}{A} \ 0 \ 0\right] \mapsto [P] = J[\sigma][F]^{-T} = \lambda \frac{A}{A_0} \text{diag}\left[\frac{F}{A\lambda} \ 0 \ 0\right] = \text{diag}\left[\frac{F}{A_0} \ 0 \ 0\right]$$

$$\text{2nd-PK: } [S] = [F]^{-1}[P] = \text{diag}\left[\frac{F}{\lambda A_0} \ 0 \ 0\right]$$

Universal solution

$$F = A\sigma_{11} = A_0 P_{11} = \lambda A_0 S_{11}$$

Example 5: Uniaxial stress (1/4)


 $\lambda = l/l_0$ axial stretch

 $\lambda_r = r/r_0$ radial stretch

$$[F] = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda_r & 0 \\ 0 & 0 & \lambda_r \end{bmatrix} \quad \underline{J} = \lambda \lambda_r^2 = \lambda \left(\frac{r}{r_0} \right)^2 = \lambda \frac{A}{A_0} = \frac{l}{l_0} \frac{A}{A_0} = \frac{V}{V_0}$$

$$[\sigma] = \text{diag}\left[\frac{F}{A} \ 0 \ 0\right] \mapsto [P] = J[\sigma][F]^{-T} = \lambda \frac{A}{A_0} \text{diag}\left[\frac{F}{A\lambda} \ 0 \ 0\right] = \text{diag}\left[\frac{F}{A_0} \ 0 \ 0\right]$$

$$\text{2nd-PK: } [S] = [F]^{-1}[P] = \text{diag}\left[\frac{F}{\lambda A_0} \ 0 \ 0\right]$$

Universal solution

$$F = A\sigma_{11} = A_0 P_{11} = \lambda A_0 S_{11}$$

Remark: 2nd-PK does not permit direct computation of stress resultants.



Example 5: Uniaxial stress (2/4)

Constitutive assumption

Hooke: $\mathbf{e} \mapsto \mathbf{S}$



Example 5: Uniaxial stress (2/4)

Constitutive assumption

Hooke: $\mathbf{e} \mapsto \mathbf{S}$

GL-tensor

$$[\mathbf{e}] = \frac{1}{2} ([\mathbf{F}]^T [\mathbf{F}] - [\mathbf{I}]) = \frac{1}{2} \text{diag}[(\lambda^2 - 1) \quad (\lambda_r^2 - 1) \quad (\lambda_r^2 - 1)]$$



Example 5: Uniaxial stress (2/4)

Constitutive assumption

$$\text{Hooke: } \mathbf{e} \mapsto \mathbf{S}$$

GL-tensor

$$[\mathbf{e}] = \frac{1}{2}([F]^T[F] - [I]) = \frac{1}{2}\text{diag}[(\lambda^2 - 1) \ (\lambda_r^2 - 1) \ (\lambda_r^2 - 1)]$$

Uniaxial stress state

$$S_{11} = E e_{11} = \frac{1}{2}E(\lambda^2 - 1)$$



Example 5: Uniaxial stress (2/4)

Constitutive assumption

Hooke: $\mathbf{e} \mapsto \mathbf{S}$

GL-tensor

$$[\mathbf{e}] = \frac{1}{2}([\mathbf{F}]^T[\mathbf{F}] - [\mathbf{I}]) = \frac{1}{2}\text{diag}[(\lambda^2 - 1) \quad (\lambda_r^2 - 1) \quad (\lambda_r^2 - 1)]$$

Uniaxial stress state

$$S_{11} = Ee_{11} = \frac{1}{2}E(\lambda^2 - 1)$$

Stress resultant

$$F = \frac{1}{2}EA_0\lambda(\lambda^2 - 1)$$



Example 5: Uniaxial stress (3/4)

Small strain approximation, $\lambda \rightarrow 1$:

Taylor series

$$F(\lambda) = \underbrace{F(1)}_0 + F'(1)(\lambda - 1) + \dots$$



Example 5: Uniaxial stress (3/4)

Small strain approximation, $\lambda \rightarrow 1$:

Taylor series

$$F(\lambda) = \underbrace{F(1)}_0 + F'(1)(\lambda - 1) + \dots$$

$$F'(1) = \frac{d}{d\lambda} \left[\frac{1}{2} E A_0 \lambda (\lambda^2 - 1) \right]_{\lambda=1} = \frac{1}{2} E A_0 (3\lambda^2 - 1) \Big|_{\lambda=1} = E A_0$$



Example 5: Uniaxial stress (3/4)

Small strain approximation, $\lambda \rightarrow 1$:

Taylor series

$$F(\lambda) = \underbrace{F(1)}_0 + F'(1)(\lambda - 1) + \dots$$

$$F'(1) = \frac{d}{d\lambda} \left[\frac{1}{2} E A_0 \lambda (\lambda^2 - 1) \right]_{\lambda=1} = \frac{1}{2} E A_0 (3\lambda^2 - 1) \Big|_{\lambda=1} = E A_0$$


Hence

$$F \simeq E A_0 (\lambda - 1) = E A_0 \frac{l - l_0}{l_0} \quad (\text{checks})$$




Example 5: Uniaxial stress (4/4)

Snap-through effect



Example 5: Uniaxial stress (4/4)

Snap-through effect



Example 5: Uniaxial stress (4/4)

Snap-through effect

