



OBJECTIVE DERIVATIVES

Jiří Plešek

Institute of Thermomechanics
Czech Academy of Sciences



Contents

- Hypoelasticity
- Rigid body motion
- Jaumann derivative
- Dienes' example
- Discussion



Material models of small strain theory

Hyperelastic

$$\sigma_{ij} = \frac{\partial \psi}{\partial \epsilon_{ij}} \Rightarrow d\sigma_{ij} = \frac{\partial^2 \psi}{\partial \epsilon_{ij} \partial \epsilon_{kl}} d\epsilon_{kl} = C_{ijkl} d\epsilon_{kl}$$



Material models of small strain theory

Hyperelastic

$$\sigma_{ij} = \frac{\partial \psi}{\partial \epsilon_{ij}} \Rightarrow \dot{\sigma}_{ij} = \frac{\partial^2 \psi}{\partial \epsilon_{ij} \partial \epsilon_{kl}} \dot{\epsilon}_{kl} = C_{ijkl} \dot{\epsilon}_{kl}$$



Material models of small strain theory

Hyperelastic

$$\sigma_{ij} = \frac{\partial \psi}{\partial \epsilon_{ij}} \Rightarrow \dot{\sigma}_{ij} = \frac{\partial^2 \psi}{\partial \epsilon_{ij} \partial \epsilon_{kl}} \dot{\epsilon}_{kl} = C_{ijkl} \dot{\epsilon}_{kl}$$

Linear elastic

$$\text{for } C_{ijkl} = \text{const.} : \sigma_{ij} = C_{ijkl} \epsilon_{kl}$$



Material models of small strain theory

Hyperelastic

$$\sigma_{ij} = \frac{\partial \psi}{\partial \epsilon_{ij}} \Rightarrow \dot{\sigma}_{ij} = \frac{\partial^2 \psi}{\partial \epsilon_{ij} \partial \epsilon_{kl}} \dot{\epsilon}_{kl} = C_{ijkl} \dot{\epsilon}_{kl}$$

Linear elastic

$$\text{for } C_{ijkl} = \text{const. : } \sigma_{ij} = C_{ijkl} \epsilon_{kl}$$

Elastic-plastic

$$\dot{\sigma}_{ij} = C_{ijkl} (\dot{\epsilon}_{kl} - \dot{\epsilon}_{kl}^p) = C_{ijkl}^{\text{ep}} \dot{\epsilon}_{kl}$$



Material models of small strain theory

Hyperelastic

$$\sigma_{ij} = \frac{\partial \psi}{\partial \epsilon_{ij}} \Rightarrow \dot{\sigma}_{ij} = \frac{\partial^2 \psi}{\partial \epsilon_{ij} \partial \epsilon_{kl}} \dot{\epsilon}_{kl} = C_{ijkl} \dot{\epsilon}_{kl}$$

Linear elastic

$$\text{for } C_{ijkl} = \text{const. : } \sigma_{ij} = C_{ijkl} \epsilon_{kl}$$

Elastic-plastic

$$\dot{\sigma}_{ij} = C_{ijkl} (\dot{\epsilon}_{kl} - \dot{\epsilon}_{kl}^p) = C_{ijkl}^{\text{ep}} \dot{\epsilon}_{kl}$$

Hypoelastic

$$\dot{\sigma}_{ij} = C_{ijkl}^{\text{hp}} \dot{\epsilon}_{kl}$$



Material models of small strain theory

Hyperelastic

$$\sigma_{ij} = \frac{\partial \psi}{\partial \epsilon_{ij}} \Rightarrow \dot{\sigma}_{ij} = \frac{\partial^2 \psi}{\partial \epsilon_{ij} \partial \epsilon_{kl}} \dot{\epsilon}_{kl} = C_{ijkl} \dot{\epsilon}_{kl}$$

Linear elastic

$$\text{for } C_{ijkl} = \text{const. : } \sigma_{ij} = C_{ijkl} \epsilon_{kl}$$

Elastic-plastic

$$\dot{\sigma}_{ij} = C_{ijkl} (\dot{\epsilon}_{kl} - \dot{\epsilon}_{kl}^p) = C_{ijkl}^{\text{ep}} \dot{\epsilon}_{kl}$$

Hypoelastic

$$\dot{\sigma} = C^{\text{hp}} \dot{\epsilon}$$

Remark: Internal friction, backstress evolution, etc.



Concept of finite strains

Generalization

$$\dot{\sigma} = C^{\text{hp}} \mathbf{D}$$



Concept of finite strains

Generalization

$$\dot{\sigma} \neq C^{\text{hp}} \mathbf{D}$$

Cauchy stress is not invariant under the rigid body motion (RBM).



Concept of finite strains

Generalization

$$\dot{\sigma} \neq C^{\text{hp}} \mathbf{D}$$

Cauchy stress is not invariant under the rigid body motion (RBM).

Denote

$$\overset{\circ}{\sigma} = C^{\text{hp}} \mathbf{D}$$

... which represents the stress rate due to straining, so that ...

$$\dot{\sigma} = \overset{\circ}{\sigma} + \text{kinematic RBM correction}$$



Concept of finite strains

Generalization

$$\dot{\sigma} \neq C^{\text{hp}} \mathbf{D}$$

Cauchy stress is not invariant under the rigid body motion (RBM).

Denote

$$\overset{\circ}{\sigma} = C^{\text{hp}} \mathbf{D}$$

... which represents the stress rate due to straining, so that ...


$$\dot{\sigma} = \overset{\circ}{\sigma} + \text{kinematic RBM correction}$$

Definition

$$\overset{\circ}{\sigma} = \dot{\sigma} - \text{kinematic RBM correction}$$

Remark: The operation $\overset{\circ}{\sigma}$ is known as the objective (time) derivative.

Rigid body motion



$$\underline{G}^+(t) = \underline{G}_0$$

$$\underline{\xi}^+ = \underline{X}$$

$$\underline{X} = \underline{O} + \underline{\xi}$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T[\sigma^+][A] = [A]^T[\sigma_0][A]$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T[\sigma^+][A] = [A]^T[\sigma_0][A]$$

Material derivative

$$[\dot{\sigma}] = [\dot{A}]^T[\sigma_0][A] + [A]^T[\sigma_0][\dot{A}]$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T[\sigma^+][A] = [A]^T[\sigma_0][A]$$

Material derivative

$$[\dot{\sigma}] = [\dot{A}]^T[\sigma_0][A] + [A]^T[\sigma_0][\dot{A}] = [\dot{A}]^T[A][\sigma] +$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T[\sigma^+][A] = [A]^T[\sigma_0][A]$$

Material derivative

$$[\dot{\sigma}] = [\dot{A}]^T[\sigma_0][A] + [A]^T[\sigma_0][\dot{A}] = [\dot{A}]^T[A][\sigma] + [\sigma][A]^T[\dot{A}]$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T [\sigma^+] [A] = [A]^T [\sigma_0] [A]$$

Material derivative

$$[\dot{\sigma}] = [\dot{A}]^T [\sigma_0] [A] + [A]^T [\sigma_0] [\dot{A}] = [\dot{A}]^T [A] [\sigma] + [\sigma] [A]^T [\dot{A}]$$

Current position vector

$$\{x\} = [A]^T \{x^+\}$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T[\sigma^+][A] = [A]^T[\sigma_0][A]$$

Material derivative

$$[\dot{\sigma}] = [\dot{A}]^T[\sigma_0][A] + [A]^T[\sigma_0][\dot{A}] = [\dot{A}]^T[A][\sigma] + [\sigma][A]^T[\dot{A}]$$

Current position vector

$$\{x\} = [A]^T\{x^+\} = [A]^T(\{\mathcal{O}^+\} + \{\xi^+\})$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T[\sigma^+][A] = [A]^T[\sigma_0][A]$$

Material derivative

$$[\dot{\sigma}] = [\dot{A}]^T[\sigma_0][A] + [A]^T[\sigma_0][\dot{A}] = [\dot{A}]^T[A][\sigma] + [\sigma][A]^T[\dot{A}]$$

Current position vector

$$\{x\} = [A]^T\{x^+\} = [A]^T(\{\mathcal{O}^+\} + \{\xi^+\}) = [A]^T(\{\mathcal{O}^+\} + \{X\})$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T [\sigma^+] [A] = [A]^T [\sigma_0] [A]$$

Material derivative

$$[\dot{\sigma}] = [\dot{A}]^T [\sigma_0] [A] + [A]^T [\sigma_0] [\dot{A}] = [\dot{A}]^T [A] [\sigma] + [\sigma] [A]^T [\dot{A}]$$

Current position vector

$$\{x\} = [A]^T \{x^+\} = [A]^T (\{\mathcal{O}^+\} + \{\xi^+\}) = [A]^T (\{\mathcal{O}^+\} + \{X\})$$

Differentiating

$$d\{x\} = [A]^T d\{X\} \Rightarrow [F] = [A]^T$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T[\sigma^+][A] = [A]^T[\sigma_0][A]$$

Material derivative

$$[\dot{\sigma}] = [\dot{A}]^T[\sigma_0][A] + [A]^T[\sigma_0][\dot{A}] = [\dot{A}]^T[A][\sigma] + [\sigma][A]^T[\dot{A}]$$

Current position vector

$$\{x\} = [A]^T\{x^+\} = [A]^T(\{\mathcal{O}^+\} + \{\xi^+\}) = [A]^T(\{\mathcal{O}^+\} + \{X\})$$

Differentiating

$$d\{x\} = [A]^T d\{X\} \Rightarrow [F] = [A]^T \Rightarrow [L] = [\dot{F}][F]^{-1} = [\dot{A}]^T[A]$$



Rigid body motion (1/2)

Cauchy stress

$$[\sigma] = [A]^T [\sigma^+] [A] = [A]^T [\sigma_0] [A]$$

Material derivative

$$[\dot{\sigma}] = [\dot{A}]^T [\sigma_0] [A] + [A]^T [\sigma_0] [\dot{A}] = [\dot{A}]^T [A] [\sigma] + [\sigma] [A]^T [\dot{A}]$$

Current position vector

$$\{x\} = [A]^T \{x^+\} = [A]^T (\{\mathcal{O}^+\} + \{\xi^+\}) = [A]^T (\{\mathcal{O}^+\} + \{X\})$$

Differentiating

$$d\{x\} = [A]^T d\{X\} \Rightarrow [F] = [A]^T \Rightarrow [L] = [\dot{F}][F]^{-1} = [\dot{A}]^T [A]$$

Hence

$$[\dot{\sigma}] = [L][\sigma] + [\sigma][L]^T$$



Rigid body motion (2/2)

Oldroyd (contravariant)

$$\dot{\sigma} = \mathbf{L}\sigma + \sigma\mathbf{L}^T \quad (\text{sym})$$



Rigid body motion (2/2)

Oldroyd (contravariant)

$$\dot{\boldsymbol{\sigma}} = \mathbf{L}\boldsymbol{\sigma} + \boldsymbol{\sigma}\mathbf{L}^T \quad (\text{sym})$$

Rate of deformation

$$[D] = \frac{1}{2}([L] + [L]^T)$$

$$= \frac{1}{2}([\dot{A}]^T[A] + [A]^T[\dot{A}])$$



Rigid body motion (2/2)

Oldroyd (contravariant)

$$\dot{\boldsymbol{\sigma}} = \mathbf{L}\boldsymbol{\sigma} + \boldsymbol{\sigma}\mathbf{L}^T \quad (\text{sym})$$

Rate of deformation

$$[D] = \frac{1}{2}([L] + [L]^T)$$

$$= \frac{1}{2}([\dot{A}]^T[A] + [A]^T[\dot{A}])$$

$$= \frac{1}{2}([A]^T[A])^\cdot = \frac{1}{2}[\dot{I}] = [0]$$



Rigid body motion (2/2)

Oldroyd (contravariant)

$$\dot{\sigma} = \mathbf{L}\sigma + \sigma\mathbf{L}^T \quad (\text{sym})$$

Rate of deformation

$$\begin{aligned} [D] &= \frac{1}{2}([L] + [L]^T) \\ &= \frac{1}{2}([\dot{A}]^T[A] + [A]^T[\dot{A}]) \\ &= \frac{1}{2}([A]^T[A])^\cdot = \frac{1}{2}[\dot{I}] = [0] \end{aligned}$$

Jaumann

$$\dot{\sigma} = \mathbf{W}\sigma - \sigma\mathbf{W} \quad (\text{sym})$$



Rigid body motion (2/2)

Oldroyd (contravariant)

$$\dot{\sigma} = \mathbf{L}\sigma + \sigma\mathbf{L}^T \quad (\text{sym})$$

Oldroyd (covariant)

$$\dot{\sigma} = -\mathbf{L}^T\sigma - \sigma\mathbf{L} \quad (\text{sym})$$

Rate of deformation

$$[D] = \frac{1}{2}([L] + [L]^T)$$

$$= \frac{1}{2}([\dot{A}]^T[A] + [A]^T[\dot{A}])$$

$$= \frac{1}{2}([A]^T[A])^\cdot = \frac{1}{2}[\dot{I}] = [0]$$

Jaumann

$$\dot{\sigma} = \mathbf{W}\sigma - \sigma\mathbf{W} \quad (\text{sym})$$



Rigid body motion (2/2)

Oldroyd (contravariant)

$$\dot{\boldsymbol{\sigma}} = \mathbf{L}\boldsymbol{\sigma} + \boldsymbol{\sigma}\mathbf{L}^T \quad (\text{sym})$$

Rate of deformation

$$[D] = \frac{1}{2}([L] + [L]^T)$$

$$= \frac{1}{2}([\dot{A}]^T[A] + [A]^T[\dot{A}])$$

$$= \frac{1}{2}([A]^T[A])^\cdot = \frac{1}{2}[\dot{I}] = [0]$$

Jaumann

$$\dot{\boldsymbol{\sigma}} = \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W} \quad (\text{sym})$$

Oldroyd (covariant)

$$\dot{\boldsymbol{\sigma}} = -\mathbf{L}^T\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{L} \quad (\text{sym})$$

Green-Naghdi

$$\mathbf{F} = \mathbf{R}\mathbf{U} = \mathbf{R} \Rightarrow \mathbf{L} = \dot{\mathbf{R}}\mathbf{R}^T = \boldsymbol{\Omega} \equiv \mathbf{W}$$



Rigid body motion (2/2)

Oldroyd (contravariant)

$$\dot{\boldsymbol{\sigma}} = \mathbf{L}\boldsymbol{\sigma} + \boldsymbol{\sigma}\mathbf{L}^T \quad (\text{sym})$$

Rate of deformation

$$[D] = \frac{1}{2}([L] + [L]^T)$$

$$= \frac{1}{2}([\dot{A}]^T[A] + [A]^T[\dot{A}])$$

$$= \frac{1}{2}([A]^T[A])^\cdot = \frac{1}{2}[\dot{I}] = [0]$$

Jaumann

$$\dot{\boldsymbol{\sigma}} = \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W} \quad (\text{sym})$$

Oldroyd (covariant)

$$\dot{\boldsymbol{\sigma}} = -\mathbf{L}^T\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{L} \quad (\text{sym})$$

Green-Naghdi

$$\mathbf{F} = \mathbf{R}\mathbf{U} = \mathbf{R} \Rightarrow \mathbf{L} = \dot{\mathbf{R}}\mathbf{R}^T = \boldsymbol{\Omega} \equiv \mathbf{W}$$

Thus

$$\dot{\boldsymbol{\sigma}} = \boldsymbol{\Omega}\boldsymbol{\sigma} - \boldsymbol{\sigma}\boldsymbol{\Omega} \quad (\text{sym})$$

Note, that GN-rate depends on \mathbf{R} , whereas the previous corrections are solely functions of \mathbf{L} .



Rigid body motion (2/2)

Oldroyd (contravariant)

$$\dot{\boldsymbol{\sigma}} = \mathbf{L}\boldsymbol{\sigma} + \boldsymbol{\sigma}\mathbf{L}^T \quad (\text{sym})$$

Rate of deformation

$$[D] = \frac{1}{2}([L] + [L]^T)$$

$$= \frac{1}{2}([\dot{A}]^T[A] + [A]^T[\dot{A}])$$

$$= \frac{1}{2}([A]^T[A])^\cdot = \frac{1}{2}[\dot{I}] = [0]$$

Jaumann

$$\dot{\boldsymbol{\sigma}} = \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W} \quad (\text{sym})$$

Oldroyd (covariant)

$$\dot{\boldsymbol{\sigma}} = -\mathbf{L}^T\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{L} \quad (\text{sym})$$

Green-Naghdi

$$\mathbf{F} = \mathbf{R}\mathbf{U} = \mathbf{R} \Rightarrow \mathbf{L} = \dot{\mathbf{R}}\mathbf{R}^T = \boldsymbol{\Omega} \equiv \mathbf{W}$$

Thus

$$\dot{\boldsymbol{\sigma}} = \boldsymbol{\Omega}\boldsymbol{\sigma} - \boldsymbol{\sigma}\boldsymbol{\Omega} \quad (\text{sym})$$

Note, that GN-rate depends on \mathbf{R} , whereas the previous corrections are solely functions of \mathbf{L} .

... and many more, e.g. Truesdell, log-spin, mixed Oldroyd (nonsym.), etc.



Zaremba-Jaumann-Noll rate (1/2)

Assume

$$\dot{\sigma} = \mathcal{L}(\mathbf{L}) = \mathcal{L}(\mathbf{D}) + \mathcal{L}(\mathbf{W})$$



Zaremba-Jaumann-Noll rate (1/2)

Assume

$$\dot{\boldsymbol{\sigma}} = \mathcal{L}(\mathbf{L}) = \mathcal{L}(\mathbf{D}) + \mathcal{L}(\mathbf{W})$$

Calibration on RBM

$$\text{for } \mathbf{D} = \mathbf{0} : \quad \mathcal{L}(\mathbf{W}) = \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W}$$



Zaremba-Jaumann-Noll rate (1/2)

Assume

$$\dot{\boldsymbol{\sigma}} = \mathcal{L}(\mathbf{L}) = \mathcal{L}(\mathbf{D}) + \mathcal{L}(\mathbf{W})$$

Calibration on RBM

$$\text{for } \mathbf{D} = \mathbf{0} : \quad \mathcal{L}(\mathbf{W}) = \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W}$$

...but $\mathcal{L}(\mathbf{W})$ is independent of \mathbf{D} , therefore

$$\dot{\boldsymbol{\sigma}} = \mathcal{L}(\mathbf{D}) + \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W}$$

Zaremba-Jaumann-Noll rate (1/2)

Assume

$$\dot{\boldsymbol{\sigma}} = \mathcal{L}(\mathbf{D}) = \mathcal{L}(\mathbf{D}) + \mathcal{L}(\mathbf{W})$$

Calibration on RBM

$$\text{for } \mathbf{D} = \mathbf{0} : \quad \mathcal{L}(\mathbf{W}) = \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W}$$

...but $\mathcal{L}(\mathbf{W})$ is independent of \mathbf{D} , therefore

$$\dot{\boldsymbol{\sigma}} = \underbrace{\mathcal{L}(\mathbf{D})}_{\dot{\boldsymbol{\sigma}}} + \underbrace{\mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W}}_{\text{RBM correction}}$$



Zaremba-Jaumann-Noll rate (1/2)

Assume

$$\dot{\boldsymbol{\sigma}} = \mathcal{L}(\mathbf{D}) = \mathcal{L}(\mathbf{D}) + \mathcal{L}(\mathbf{W})$$

Calibration on RBM

$$\text{for } \mathbf{D} = \mathbf{0} : \quad \mathcal{L}(\mathbf{W}) = \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W}$$

...but $\mathcal{L}(\mathbf{W})$ is independent of \mathbf{D} , therefore

$$\dot{\boldsymbol{\sigma}} = \underbrace{\mathcal{L}(\mathbf{D})}_{\overset{\circ}{\boldsymbol{\sigma}}} + \underbrace{\mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W}}_{\text{RBM correction}}$$

Zaremba(1903), Jaumman (1911), Noll(1940)

$$\overset{\circ}{\boldsymbol{\sigma}} = \dot{\boldsymbol{\sigma}} - \mathbf{W}\boldsymbol{\sigma} + \boldsymbol{\sigma}\mathbf{W} \quad (\text{sym})$$



Zaremba-Jaumann-Noll rate (2/2)

Algorithm:

1. $\mathbf{L} = \mathbf{D} + \mathbf{W}$

2. $\overset{\circ}{\boldsymbol{\sigma}} = \mathbf{C}^{\text{hp}} \mathbf{D}$ (constitutive equations)

3. $\dot{\boldsymbol{\sigma}} = \overset{\circ}{\boldsymbol{\sigma}} + \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W}$



Zaremba-Jaumann-Noll rate (2/2)


Algorithm:

1. $\mathbf{L} = \mathbf{D} + \mathbf{W}$
2. $\dot{\boldsymbol{\sigma}} = \mathbf{C}^{\text{hp}} \mathbf{D}$ (constitutive equations)
3. $\dot{\boldsymbol{\sigma}} = \dot{\boldsymbol{\sigma}} + \mathbf{W}\boldsymbol{\sigma} - \boldsymbol{\sigma}\mathbf{W}$

Remarks

- Derivation of ZJN derivative is rigorous.
- ZJN based CE are correct and useful.
- Oldroyd derivatives are equivalent.
- GN derivative is not equivalent as it depends on the reference configuration.

Example 3: Dienes (1979)




$$u_1 = X_2 \tan \gamma$$

$$u_2 = 0$$



Example 3: Dienes (1979)




$$u_1 = X_2 kt$$

$$u_2 = 0$$




Example 3: Dienes (1979)



$$u_1 = X_2 kt \Rightarrow v_1 = kX_2 = kx_2$$

$$u_2 = 0 \Rightarrow v_2 = 0$$

Example 3: Dienes (1979)




$$u_1 = X_2 k t \Rightarrow v_1 = k X_2 = k x_2$$

$$u_2 = 0 \Rightarrow v_2 = 0$$

Universal solution for simple shear

$$[L] = \begin{bmatrix} 0 & k \\ 0 & 0 \end{bmatrix} \quad [D] = \frac{k}{2} \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \quad [W] = \frac{k}{2} \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$$

Example 3: Dienes (1979)



$$u_1 = X_2 k t \Rightarrow v_1 = k X_2 = k x_2$$

$$u_2 = 0 \Rightarrow v_2 = 0$$

Universal solution for simple shear

$$[L] = \begin{bmatrix} 0 & k \\ 0 & 0 \end{bmatrix} \quad [D] = \frac{k}{2} \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \quad [W] = \frac{k}{2} \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$$

$$[W][\sigma] - [\sigma][W] = \frac{k}{2} \begin{bmatrix} 2\sigma_{21} & \sigma_{22} - \sigma_{11} \\ \sigma_{22} - \sigma_{11} & -2\sigma_{12} \end{bmatrix} \quad (\text{sym})$$



Example 3: Dienes (1979)

Hypoelastic eqn. of degree zero with Lamé's constants

$$\overset{\circ}{\boldsymbol{\sigma}} = \lambda \operatorname{tr}(\mathbf{D})\mathbf{I} + 2\mu\mathbf{D}$$



Example 3: Dienes (1979)

Hypoelastic eqn. of degree zero with Lamé's constants

$$\overset{\circ}{\boldsymbol{\sigma}} = \lambda \operatorname{tr}(\mathbf{D})\mathbf{I} + 2\mu\mathbf{D}$$

In particular

$$[\overset{\circ}{\sigma}] = [0] + \mu k \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$$



Example 3: Dienes (1979)

Hypoelastic eqn. of degree zero with Lamé's constants

$$\overset{\circ}{\boldsymbol{\sigma}} = \lambda \operatorname{tr}(\mathbf{D})\mathbf{I} + 2\mu\mathbf{D}$$

In particular

$$[\overset{\circ}{\boldsymbol{\sigma}}] = [0] + \mu k \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$$

Adding ZJN correction

$$\begin{bmatrix} \dot{\sigma}_{11} & \dot{\sigma}_{12} \\ \dot{\sigma}_{21} & \dot{\sigma}_{22} \end{bmatrix} = \mu k \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} + \frac{k}{2} \begin{bmatrix} 2\sigma_{21} & \sigma_{22} - \sigma_{11} \\ \sigma_{22} - \sigma_{11} & -2\sigma_{12} \end{bmatrix}$$



Example 3: Dienes (1979)

Hypoelastic eqn. of degree zero with Lamé's constants

$$\overset{\circ}{\boldsymbol{\sigma}} = \lambda \operatorname{tr}(\mathbf{D})\mathbf{I} + 2\mu\mathbf{D}$$

In particular

$$[\overset{\circ}{\boldsymbol{\sigma}}] = [0] + \mu k \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$$

Adding ZJN correction

$$\begin{bmatrix} \dot{\sigma}_{11} & \dot{\sigma}_{12} \\ \dot{\sigma}_{21} & \dot{\sigma}_{22} \end{bmatrix} = \mu k \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} + \frac{k}{2} \begin{bmatrix} 2\sigma_{21} & \sigma_{22} - \sigma_{11} \\ \sigma_{22} - \sigma_{11} & -2\sigma_{12} \end{bmatrix}$$

Only the specification of objective rate completes the CE. Here we chose ZJN.



Example 3: Dienes (1979)

System of three ODE to solve:

$$\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}, \quad \dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})$$



Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\dot{\sigma}_{11} + \dot{\sigma}_{22} = 0}, \quad \dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})$$



Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\sigma_{11} + \sigma_{22} = \text{const.}}, \quad \dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})$$



Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\sigma_{11} + \sigma_{22} = \text{const.}}, \quad \dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})$$

Initial condition at $t = 0$: $\sigma_{11} + \sigma_{22} = 0$



Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\sigma_{11} + \sigma_{22} = 0}, \quad \underbrace{\dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})}_{\mu k + k\sigma_{22}}$$

Initial condition at $t = 0$: $\sigma_{11} + \sigma_{22} = 0$

Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\sigma_{11} + \sigma_{22} = 0}, \quad \underbrace{\dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})}_{\mu k + k\sigma_{22}}$$

Initial condition at $t = 0$: $\sigma_{11} + \sigma_{22} = 0$

Differentiating the last eqn. and substituting from the second:

$$\ddot{\sigma}_{12} = k\dot{\sigma}_{22} = -k^2\sigma_{12} \Rightarrow \ddot{\sigma}_{12} + k^2\sigma_{12} = 0$$



Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\sigma_{11} + \sigma_{22} = 0}, \quad \underbrace{\dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})}_{\mu k + k\sigma_{22}}$$

Initial condition at $t = 0$: $\sigma_{11} + \sigma_{22} = 0$

Differentiating the last eqn. and substituting from the second:

$$\ddot{\sigma}_{12} = k\dot{\sigma}_{22} = -k^2\sigma_{12} \Rightarrow \ddot{\sigma}_{12} + k^2\sigma_{12} = 0$$

Solution

$$\sigma_{12} = A \cos kt + B \sin kt$$



Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\sigma_{11} + \sigma_{22} = 0}, \quad \underbrace{\dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})}_{\mu k + k\sigma_{22}}$$

Initial condition at $t = 0$: $\sigma_{11} + \sigma_{22} = 0$

Differentiating the last eqn. and substituting from the second:

$$\ddot{\sigma}_{12} = k\dot{\sigma}_{22} = -k^2\sigma_{12} \Rightarrow \ddot{\sigma}_{12} + k^2\sigma_{12} = 0$$

Solution

$$\sigma_{12} = B \sin kt$$

Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\sigma_{11} + \sigma_{22} = 0}, \quad \underbrace{\dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})}_{\mu k + k\sigma_{22}}$$

Initial condition at $t = 0$: $\sigma_{11} + \sigma_{22} = 0$

Differentiating the last eqn. and substituting from the second:

$$\ddot{\sigma}_{12} = k\dot{\sigma}_{22} = -k^2\sigma_{12} \Rightarrow \ddot{\sigma}_{12} + k^2\sigma_{12} = 0$$

Solution

$$\sigma_{12} = B \sin kt$$

Using the last eqn.: $\sigma_{22} = -\mu + \frac{1}{k}\dot{\sigma}_{12} = -\mu + B \cos kt$

Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\sigma_{11} + \sigma_{22} = 0}, \quad \underbrace{\dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})}_{\mu k + k\sigma_{22}}$$

Initial condition at $t = 0$: $\sigma_{11} + \sigma_{22} = 0$

Differentiating the last eqn. and substituting from the second:

$$\ddot{\sigma}_{12} = k\dot{\sigma}_{22} = -k^2\sigma_{12} \Rightarrow \ddot{\sigma}_{12} + k^2\sigma_{12} = 0$$

Solution

$$\sigma_{12} = B \sin kt$$

Using the last eqn.: $\sigma_{22} = -\mu + \frac{1}{k}\dot{\sigma}_{12} = -\mu + B \cos kt$

Initial condition at $t = 0$: $\sigma_{22} = -\mu + B = 0$

Example 3: Dienes (1979)

System of three ODE to solve:

$$\underbrace{\dot{\sigma}_{11} = k\sigma_{21}, \quad \dot{\sigma}_{22} = -k\sigma_{12}}_{\sigma_{11} + \sigma_{22} = 0}, \quad \underbrace{\dot{\sigma}_{12} = \mu k + \frac{k}{2}(\sigma_{22} - \sigma_{11})}_{\mu k + k\sigma_{22}}$$

Initial condition at $t = 0$: $\sigma_{11} + \sigma_{22} = 0$

Differentiating the last eqn. and substituting from the second:

$$\ddot{\sigma}_{12} = k\dot{\sigma}_{22} = -k^2\sigma_{12} \Rightarrow \ddot{\sigma}_{12} + k^2\sigma_{12} = 0$$

Solution

$$\sigma_{12} = \mu \sin kt$$

Using the last eqn.: $\sigma_{22} = -\mu + \frac{1}{k}\dot{\sigma}_{12} = -\mu + B \cos kt$

Initial condition at $t = 0$: $\sigma_{22} = -\mu + B = 0 \Rightarrow \sigma_{22} = \mu(-1 + \cos kt)$



Example 3: Dienes (1979)

ZJN solution

$$\sigma_{11} = -\sigma_{22} = \mu(1 - \cos kt)$$


$$\sigma_{12} = \mu \sin kt$$

Example 3: Dienes (1979)

ZJN solution

$$\sigma_{11} = -\sigma_{22} = \mu(1 - \cos kt)$$

$$\sigma_{12} = \mu \sin kt$$






Example 3: Dienes (1979)

ZJN solution

$$\sigma_{11} = -\sigma_{22} = \mu(1 - \cos kt)$$

$$\sigma_{12} = \mu \sin kt$$



Only valid for reasonable shear angle, i.e., good for most engineering problems.



Conclusions

- Dienes (1979) proposed the use of GN-rate, which was later disputed by Halleux and Donea (1986).
- In fact, Simo and Pister (1984) proved that no commonly known stress rate enables to recover reversible elastic response from the hypoelastic equation of degree zero.
- Inconclusive proof of integrability was supplied by Xiao, Bruhns and Meyers (1999) for the log-spin rate.



Conclusions

- Dienes (1979) proposed the use of GN-rate, which was later disputed by Halleux and Donea (1986).
- In fact, Simo and Pister (1984) proved that no commonly known stress rate enables to recover reversible elastic response from the hypoelastic equation of degree zero.
- Inconclusive proof of integrability was supplied by Xiao, Bruhns and Meyers (1999) for the log-spin rate.
- It is difficult to propose a suitable C^{hp} for ZJN rate, unless it follows directly from the free energy (i.e., it is not hypoelastic) or one has already set up C^{hp} for a different objective rate, which then needs merely to be converted.



Conclusions

- Dienes (1979) proposed the use of GN-rate, which was later disputed by Halleux and Donea (1986).
- In fact, Simo and Pister (1984) proved that no commonly known stress rate enables to recover reversible elastic response from the hypoelastic equation of degree zero.
- Inconclusive proof of integrability was supplied by Xiao, Bruhns and Meyers (1999) for the log-spin rate.
- It is difficult to propose a suitable C^{hp} for ZJN rate, unless it follows directly from the free energy (i.e., it is not hypoelastic) or one has already set up C^{hp} for a different objective rate, which then needs merely to be converted.
- ZJN rate is required as an output parameter of the UMAT procedure, which poses less of a problem than often thought.