



NUMERICAL INTEGRATION

Jiří Plešek

Institute of Thermomechanics
Czech Academy of Sciences



Contents

- Equations of incremental plasticity
- Methods & Bibliography
- Numerical stability
 - explicit approach
 - implicit approach



Voigt's notation (1/2)

Stress six-vector

$$\boldsymbol{\sigma} = [\sigma_{11} \ \sigma_{22} \ \sigma_{33} \ \sigma_{23} \ \sigma_{13} \ \sigma_{12}]^T$$



Voigt's notation (1/2)

Stress six-vector

$$\boldsymbol{\sigma} = [\sigma_{11} \ \sigma_{22} \ \sigma_{33} \ \sigma_{23} \ \sigma_{13} \ \sigma_{12}]^T$$

Strain

$$\boldsymbol{\epsilon} = [\epsilon_{11} \ \epsilon_{22} \ \epsilon_{33} \ 2\epsilon_{23} \ 2\epsilon_{13} \ 2\epsilon_{12}]^T$$



Voigt's notation (1/2)

Stress six-vector

$$\boldsymbol{\sigma} = [\sigma_{11} \ \sigma_{22} \ \sigma_{33} \ \sigma_{23} \ \sigma_{13} \ \sigma_{12}]^T$$

Strain

$$\boldsymbol{\epsilon} = [\epsilon_{11} \ \epsilon_{22} \ \epsilon_{33} \ 2\epsilon_{23} \ 2\epsilon_{13} \ 2\epsilon_{12}]^T$$

Hooke's law

$$\boldsymbol{\sigma} = \mathbf{C}\boldsymbol{\epsilon}^e, \quad \text{where } \mathbf{C}(6 \times 6) \text{ sym+def}$$



Voigt's notation (1/2)

Stress six-vector

$$\boldsymbol{\sigma} = [\sigma_{11} \ \sigma_{22} \ \sigma_{33} \ \sigma_{23} \ \sigma_{13} \ \sigma_{12}]^T$$

Strain

$$\boldsymbol{\epsilon} = [\epsilon_{11} \ \epsilon_{22} \ \epsilon_{33} \ 2\epsilon_{23} \ 2\epsilon_{13} \ 2\epsilon_{12}]^T$$

Hooke's law

$$\boldsymbol{\sigma} = \mathbf{C}\boldsymbol{\epsilon}^e, \quad \text{where } \mathbf{C}(6 \times 6) \text{ sym+def}$$

Gradient

$$\mathbf{g} = \left[\frac{\partial F}{\partial \sigma_{11}} \ \frac{\partial F}{\partial \sigma_{22}} \ \frac{\partial F}{\partial \sigma_{33}} \ 2\frac{\partial F}{\partial \sigma_{23}} \ 2\frac{\partial F}{\partial \sigma_{13}} \ 2\frac{\partial F}{\partial \sigma_{12}} \right]^T$$



Voigt's notation (2/2)

Consistency

$$\dot{F} = \frac{\partial F}{\partial \sigma_{ij}} \dot{\sigma}_{ij} = \mathbf{g}^T \dot{\boldsymbol{\sigma}} = \mathbf{g}^T \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = 0$$



Voigt's notation (2/2)

Consistency

$$\dot{F} = \frac{\partial F}{\partial \sigma_{ij}} \dot{\sigma}_{ij} = \mathbf{g}^T \dot{\boldsymbol{\sigma}} = \mathbf{g}^T \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = 0$$

Flow rule

$$\dot{\boldsymbol{\epsilon}}^p = \lambda \mathbf{R} \quad (\text{set } \mathbf{R} = \mathbf{g} \text{ for association})$$



Voigt's notation (2/2)

Consistency

$$\dot{F} = \frac{\partial F}{\partial \sigma_{ij}} \dot{\sigma}_{ij} = \mathbf{g}^T \dot{\boldsymbol{\sigma}} = \mathbf{g}^T \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = 0$$

Flow rule

$$\dot{\boldsymbol{\epsilon}}^p = \lambda \mathbf{R} \quad (\text{set } \mathbf{R} = \mathbf{g} \text{ for association})$$

Plastic multiplier

$$\lambda = \frac{\mathbf{g}^T \mathbf{C} \dot{\boldsymbol{\epsilon}}}{\mathbf{g}^T \mathbf{C} \mathbf{R}} \geq 0$$

Voigt's notation (2/2)

Consistency

$$\dot{F} = \frac{\partial F}{\partial \sigma_{ij}} \dot{\sigma}_{ij} = \mathbf{g}^T \dot{\boldsymbol{\sigma}} = \mathbf{g}^T \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = 0$$

Flow rule

$$\dot{\boldsymbol{\epsilon}}^p = \lambda \mathbf{R} \quad (\text{set } \mathbf{R} = \mathbf{g} \text{ for association})$$

Plastic multiplier

$$\lambda = \frac{\mathbf{g}^T \mathbf{C} \dot{\boldsymbol{\epsilon}}}{\mathbf{g}^T \mathbf{C} \mathbf{R}} \geq 0$$

Stress rate

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \lambda \mathbf{R})$$

Voigt's notation (2/2)

Consistency

$$\dot{F} = \frac{\partial F}{\partial \sigma_{ij}} \dot{\sigma}_{ij} = \mathbf{g}^T \dot{\boldsymbol{\sigma}} = \mathbf{g}^T \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = 0$$

Flow rule

$$\dot{\boldsymbol{\epsilon}}^p = \lambda \mathbf{R} \quad (\text{set } \mathbf{R} = \mathbf{g} \text{ for association})$$

Plastic multiplier

$$\lambda = \frac{\mathbf{g}^T \mathbf{C} \dot{\boldsymbol{\epsilon}}}{\mathbf{g}^T \mathbf{C} \mathbf{R}} \geq 0$$

Stress rate

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \lambda \mathbf{R}) = \mathbf{C} \dot{\boldsymbol{\epsilon}} - \mathbf{C} \mathbf{R} \lambda$$

Voigt's notation (2/2)

Consistency

$$\dot{F} = \frac{\partial F}{\partial \sigma_{ij}} \dot{\sigma}_{ij} = \mathbf{g}^T \dot{\boldsymbol{\sigma}} = \mathbf{g}^T \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = 0$$

Flow rule

$$\dot{\boldsymbol{\epsilon}}^p = \lambda \mathbf{R} \quad (\text{set } \mathbf{R} = \mathbf{g} \text{ for association})$$

Plastic multiplier

$$\lambda = \frac{\mathbf{g}^T \mathbf{C} \dot{\boldsymbol{\epsilon}}}{\mathbf{g}^T \mathbf{C} \mathbf{R}} \geq 0$$

Stress rate

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \lambda \mathbf{R}) = \mathbf{C} \dot{\boldsymbol{\epsilon}} - \mathbf{C} \mathbf{R} \lambda = \left(\mathbf{C} - \frac{\mathbf{C} \mathbf{R} \mathbf{g}^T \mathbf{C}}{\mathbf{g}^T \mathbf{C} \mathbf{R}} \right) \dot{\boldsymbol{\epsilon}}$$

Voigt's notation (2/2)

Consistency

$$\dot{F} = \frac{\partial F}{\partial \sigma_{ij}} \dot{\sigma}_{ij} = \mathbf{g}^T \dot{\boldsymbol{\sigma}} = \mathbf{g}^T \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = 0$$

Flow rule

$$\dot{\boldsymbol{\epsilon}}^p = \lambda \mathbf{R} \quad (\text{set } \mathbf{R} = \mathbf{g} \text{ for association})$$

Plastic multiplier

$$\lambda = \frac{\mathbf{g}^T \mathbf{C} \dot{\boldsymbol{\epsilon}}}{\mathbf{g}^T \mathbf{C} \mathbf{R}} \geq 0$$

Stress rate

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \lambda \mathbf{R}) = \mathbf{C} \dot{\boldsymbol{\epsilon}} - \mathbf{C} \mathbf{R} \lambda = \underbrace{\left(\mathbf{C} - \frac{\mathbf{C} \mathbf{R} \mathbf{g}^T \mathbf{C}}{\mathbf{g}^T \mathbf{C} \mathbf{R}} \right)}_{\mathbf{C}^{\text{ep}}} \dot{\boldsymbol{\epsilon}}$$

Voigt's notation (2/2)

Consistency

$$\dot{F} = \frac{\partial F}{\partial \sigma_{ij}} \dot{\sigma}_{ij} = \mathbf{g}^T \dot{\boldsymbol{\sigma}} = \mathbf{g}^T \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = 0$$

Flow rule

$$\dot{\boldsymbol{\epsilon}}^p = \lambda \mathbf{R} \quad (\text{set } \mathbf{R} = \mathbf{g} \text{ for association})$$

Plastic multiplier

$$\lambda = \frac{\mathbf{g}^T \mathbf{C} \dot{\boldsymbol{\epsilon}}}{\mathbf{g}^T \mathbf{C} \mathbf{R}} \geq 0$$

Stress rate

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \dot{\boldsymbol{\epsilon}}^p) = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \lambda \mathbf{R}) = \mathbf{C} \dot{\boldsymbol{\epsilon}} - \mathbf{C} \mathbf{R} \lambda = \underbrace{\left(\mathbf{C} - \frac{\mathbf{C} \mathbf{R} \mathbf{g}^T \mathbf{C}}{\mathbf{g}^T \mathbf{C} \mathbf{R}} \right)}_{\mathbf{C}^{\text{ep}}} \dot{\boldsymbol{\epsilon}}$$

For symmetry, $\mathbf{R} = \mathbf{g}$.

Remark: UMAT output to enter the Newton-Raphson procedure.



The algebro-differential problem

Stress increment

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \lambda \mathbf{R})$$

subject to

$$F(\boldsymbol{\sigma}) = 0$$



The algebro-differential problem

Stress increment

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \lambda \mathbf{R})$$

subject to

$$F(\boldsymbol{\sigma}) = 0$$

The latter may be replaced by $\dot{F} = 0$ leading to

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}^{\text{ep}} \dot{\boldsymbol{\epsilon}} = \mathbf{r}(\boldsymbol{\sigma}, t)$$



The algebro-differential problem

Stress increment

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}(\dot{\boldsymbol{\epsilon}} - \lambda \mathbf{R})$$

subject to

$$F(\boldsymbol{\sigma}) = 0$$

The latter may be replaced by $\dot{F} = 0$ leading to

$$\dot{\boldsymbol{\sigma}} = \mathbf{C}^{\text{ep}} \dot{\boldsymbol{\epsilon}} = \mathbf{r}(\boldsymbol{\sigma}, t)$$

- Plešek, J.: Numerická integrace konstitutivních vztahů. Inž. mech., 6, No. 1, pp. 3–24, 1999.
- Plešek, J., Křístek, A.: Assessment of methods for locating the point of initial yield. Comp. Meth. Appl. Mech. Engrg., 141, pp. 389–397, 1997.



Three commandments

1. Robustness is what an engineer really needs, putting the notion of method's accuracy on the back burner. Besides, 'accurate' does not necessarily mean 'effective.'



Three commandments

1. Robustness is what an engineer really needs, putting the notion of method's accuracy on the back burner. Besides, 'accurate' does not necessarily mean 'effective.'
2. Linear, single step methods are preferred in FEM due to the method's heavy data traffic.



Three commandments

1. Robustness is what an engineer really needs, putting the notion of method's accuracy on the back burner. Besides, 'accurate' does not necessarily mean 'effective.'
2. Linear, single step methods are preferred in FEM due to the method's heavy data traffic.
3. Numerical stability of time marching schemes refers to the way a method handles passing of round-off errors from one step to another.




Three commandments

1. Robustness is what an engineer really needs, putting the notion of method's accuracy on the back burner. Besides, 'accurate' does not necessarily mean 'effective.'
 2. Linear, single step methods are preferred in FEM due to the method's heavy data traffic.
 3. Numerical stability of time marching schemes refers to the way a method handles passing of round-off errors from one step to another.
- Lambert, J.D.: *Numerical Methods for Ordinary Differential Systems*. Wiley, ISBN 0-471-92990-5, Chichester 1993.

Mathematical stability

ODE: $\dot{y} = \lambda y$, $\lambda \in \mathbb{R} \Rightarrow$

$$y(t) = y_0 e^{\lambda t}$$



Ljapunov stability: perturbation of initial conditions.



Explicit scheme

Euler forward

$$y_{n+1} = y_n + \dot{y}_n \Delta t$$



Explicit scheme

Euler forward

$$y_{n+1} = y_n + \dot{y}_n \Delta t = y_n + \lambda y_n \Delta t$$



Explicit scheme

Euler forward

$$y_{n+1} = y_n + \dot{y}_n \Delta t = y_n + \lambda y_n \Delta t = (1 + \lambda \Delta t) y_n$$



Explicit scheme

Euler forward

$$y_{n+1} = y_n + \dot{y}_n \Delta t = y_n + \lambda y_n \Delta t = (1 + \lambda \Delta t) y_n$$

Round-off error attenuation

$$|1 + \lambda \Delta t| < 1$$



Explicit scheme

Euler forward

$$y_{n+1} = y_n + \dot{y}_n \Delta t = y_n + \lambda y_n \Delta t = (1 + \lambda \Delta t) y_n$$

Round-off error attenuation

$$|1 + \lambda \Delta t| < 1$$

Assuming math stability


$$\Delta t < \Delta t_{\text{crit}} = \frac{2}{|\lambda|}$$

The Euler forward method is said to be conditionally stable.

Explicit scheme

Example: $\Delta t = 1.5 \Delta t_{\text{crit}} = \frac{3}{|\lambda|}$

$$y_{n+1} = \left(1 + \lambda \frac{3}{|\lambda|}\right) y_n = -2y_n$$



for $n=10$: $2^{10} = 1024 \Rightarrow$ for $n=50$: $2^{50} \approx 10^{15}$ (killing solution)

Remark: one unstable harmonic is sufficient to explode SODE.



Implicit scheme

Euler backward

$$y_{n+1} = y_n + \dot{y}_{n+1}\Delta t = y_n + \lambda y_{n+1}\Delta t$$

Recurrent formula

$$y_{n+1} = \frac{y_n}{1 - \lambda\Delta t}$$

The Euler backward method is said to be unconditionally stable.



Implicit scheme

Euler backward

$$y_{n+1} = y_n + \dot{y}_{n+1}\Delta t = y_n + \lambda y_{n+1}\Delta t$$

Recurrent formula

$$y_{n+1} = \frac{y_n}{1 - \lambda\Delta t}$$


The Euler backward method is said to be unconditionally stable.

- Both methods have the same (first order or linear) accuracy, the only difference being their stability.

Implicit scheme

Example: $\lambda \Delta t = -3$ (as before)

$$y_{n+1} = \frac{y_n}{1 - \lambda \Delta t} = \frac{1}{4} y_n$$



Remark: fast convergence toward static solution for $\Delta t \rightarrow \infty$.

Newmark method, IXR method ...



A less known deficiency

Fixed point iteration

$$y_{n+1}^{(i+1)} = y_n + \lambda y_{n+1}^{(i)} \Delta t$$



A less known deficiency

Fixed point iteration

$$y_{n+1}^{(i+1)} = y_n + \lambda y_{n+1}^{(i)} \Delta t$$

Spectral radius

$$|\lambda \Delta t| < 1$$



A less known deficiency

Fixed point iteration

$$y_{n+1}^{(i+1)} = y_n + \lambda y_{n+1}^{(i)} \Delta t$$

Spectral radius

$$|\lambda \Delta t| < 1$$

Convergence condition

$$\Delta t < \frac{1}{|\lambda|} = \frac{1}{2} \Delta t_{\text{crit}}$$

Remark: The critical time step is half the size of that of the Euler forward method!



Sets of ODE

Plasticity equations

$$\dot{\sigma} = \mathbf{r}(\sigma, t)$$



Sets of ODE

Plasticity equations

$$\dot{\boldsymbol{\sigma}} = \mathbf{r}(\boldsymbol{\sigma}, t)$$

may, first, be linearized as $\mathcal{E}rror \rightarrow 0$ and, second, decoupled by the spectral decomposition to obtain

$$\mathbf{J} = \frac{\partial \mathbf{r}}{\partial \boldsymbol{\sigma}} \quad \text{and} \quad |\lambda|_{\max} = \max_i |\lambda_i|$$



Sets of ODE

Plasticity equations

$$\dot{\boldsymbol{\sigma}} = \mathbf{r}(\boldsymbol{\sigma}, t)$$

may, first, be linearized as $\mathcal{E}_{\text{error}} \rightarrow 0$ and, second, decoupled by the spectral decomposition to obtain

$$\mathbf{J} = \frac{\partial \mathbf{r}}{\partial \boldsymbol{\sigma}} \quad \text{and} \quad |\lambda|_{\max} = \max_i |\lambda_i|$$

A-stability condition

$$\Delta t < \frac{2}{|\lambda|_{\max}}$$

B-stability would treat the former fully non-linear operator \mathbf{r} .



Sets of ODE

Plasticity equations

$$\dot{\boldsymbol{\sigma}} = \mathbf{r}(\boldsymbol{\sigma}, t)$$

may, first, be linearized as $\mathcal{E}_{\text{error}} \rightarrow 0$ and, second, decoupled by the spectral decomposition to obtain

$$\mathbf{J} = \frac{\partial \mathbf{r}}{\partial \boldsymbol{\sigma}} \quad \text{and} \quad |\lambda|_{\max} = \max_i |\lambda_i|$$

A-stability condition

$$\Delta t < \frac{2}{|\lambda|_{\max}}$$

B-stability would treat the former fully non-linear operator \mathbf{r} .

Remark: $|\lambda|_{\max}$ is seldom known beforehand, leaving us with experimentation.



Concluding remarks

- Explicit methods are by far better (Plešek :-). They are much easier to handle, require less number of FLOP and offer straightforward approach to coupled problems.



Concluding remarks

- Explicit methods are by far better (Plešek :-). They are much easier to handle, require less number of FLOP and offer straightforward approach to coupled problems.
- Disadvantage being the lack of information on Δt_{crit} , which, in fact, necessitates the introduction of adaptive time step control. This is especially true of integrating the so called stiff systems.
- Plešek, J., Korouš, J.: Explicit integration method with time step control for viscoplasticity and creep. Adv. Engrg. Software, **33**, No. 7–10, pp. 621–630, 2002.



Concluding remarks

- Explicit methods are by far better (Plešek :-). They are much easier to handle, require less number of FLOP and offer straightforward approach to coupled problems.
- Disadvantage being the lack of information on Δt_{crit} , which, in fact, necessitates the introduction of adaptive time step control. This is especially true of integrating the so called stiff systems.
- Plešek, J., Korouš, J.: Explicit integration method with time step control for viscoplasticity and creep. Adv. Engrg. Software, **33**, No. 7–10, pp. 621–630, 2002.
- One boast of implicit schemes is the built in early warning mechanism triggered by the divergence of the inner iteration loop. This is usually dealt with by halving the integration step. The integration is, thus, less efficient but able to run in a fully automated mode.