



YIELDING FUNCTIONS I

Jiří Plešek

Institute of Thermomechanics
Czech Academy of Sciences



Contents

- Review
- Deviatoric stress
- Mechanism of plastic slip
- Von Mises' criterion
- Influence of hydrostatic pressure
- Yield stress in tension and compression



Review

Yield function

$$F(\sigma_{ij}) = f(\sigma_{ij}) - \sigma_Y \leq 0$$

Noteworthy properties

- Convexity
- Hydrostatic sensitivity
- Tension versus compression



Deviatoric stress

Mean stress

$$\sigma_m = \frac{1}{3}(\sigma_{11} + \sigma_{22} + \sigma_{33})$$



Deviatoric stress

Mean stress

$$\sigma_m = \frac{1}{3}(\sigma_{11} + \sigma_{22} + \sigma_{33})$$

Stress deviator tensor

$$\mathbf{S} = \boldsymbol{\sigma} - \sigma_m \mathbf{I}$$



Deviatoric stress

Mean stress

$$\sigma_m = \frac{1}{3}(\sigma_{11} + \sigma_{22} + \sigma_{33})$$

Stress deviator tensor

$$\mathbf{S} = \boldsymbol{\sigma} - \sigma_m \mathbf{I}$$

Theorem of zero trace

$$S_m = \sigma_m - \sigma_m \frac{1}{3}(1 + 1 + 1) = 0$$



Deviatoric stress

Mean stress

$$\sigma_m = \frac{1}{3}(\sigma_{11} + \sigma_{22} + \sigma_{33})$$

Stress deviator tensor

$$\mathbf{S} = \boldsymbol{\sigma} - \sigma_m \mathbf{I}$$


Theorem of zero trace

$$S_m = \sigma_m - \sigma_m \frac{1}{3}(1 + 1 + 1) = 0$$


Deviatoric split

$$F(\sigma_{ij}) = F(S_{ij}, \sigma_m)$$


Pascal's law





Pascal's law




Mohr's diagram



Thought experiment



Thought experiment



$$\underline{\underline{\sigma}} = \begin{bmatrix} -107 & 0 & 0 \\ 0 & -110 & 0 \\ 0 & 0 & -110 \end{bmatrix}$$

$$\sigma_m = -109$$

$$\underline{\underline{s}} = \begin{bmatrix} 2 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 0 & -1 \end{bmatrix}$$

$$s_m = 0 \quad (\text{checks})$$



Effect of pressure variation

$$\text{Let } \hat{\sigma} = \sigma - p\mathbf{I} \quad \Rightarrow \quad \hat{\sigma}_m = \sigma_m - p$$



Effect of pressure variation

$$\text{Let } \hat{\sigma} = \sigma - p\mathbf{I} \quad \Rightarrow \quad \hat{\sigma}_m = \sigma_m - p$$

Deviatoric stress

$$\hat{S} = \hat{\sigma} - \hat{\sigma}_m \mathbf{I}$$



Effect of pressure variation

$$\text{Let } \hat{\boldsymbol{\sigma}} = \boldsymbol{\sigma} - p\mathbf{I} \quad \Rightarrow \quad \hat{\sigma}_m = \sigma_m - p$$

Deviatoric stress

$$\hat{\mathbf{S}} = \hat{\boldsymbol{\sigma}} - \hat{\sigma}_m\mathbf{I} = \boldsymbol{\sigma} - p\mathbf{I} - (\sigma_m - p)\mathbf{I}$$



Effect of pressure variation

$$\text{Let } \hat{\boldsymbol{\sigma}} = \boldsymbol{\sigma} - p\mathbf{I} \quad \Rightarrow \quad \hat{\sigma}_m = \sigma_m - p$$

Deviatoric stress

$$\hat{\mathbf{S}} = \hat{\boldsymbol{\sigma}} - \hat{\sigma}_m\mathbf{I} = \boldsymbol{\sigma} - p\mathbf{I} - (\sigma_m - p)\mathbf{I} = \boldsymbol{\sigma} - \sigma_m\mathbf{I} = \mathbf{S}$$



Effect of pressure variation

Let $\hat{\sigma} = \sigma - p\mathbf{I} \Rightarrow \hat{\sigma}_m = \sigma_m - p$

Deviatoric stress

$$\hat{\mathbf{S}} = \hat{\sigma} - \hat{\sigma}_m \mathbf{I} = \sigma - p\mathbf{I} - (\sigma_m - p)\mathbf{I} = \sigma - \sigma_m \mathbf{I} = \mathbf{S}$$

Thus we have

$$F(\hat{\sigma}_{ij}) = F(S_{ij}, \sigma_m - p)$$



Effect of pressure variation

$$\text{Let } \hat{\boldsymbol{\sigma}} = \boldsymbol{\sigma} - p\mathbf{I} \quad \Rightarrow \quad \hat{\sigma}_m = \sigma_m - p$$

Deviatoric stress

$$\hat{\mathbf{S}} = \hat{\boldsymbol{\sigma}} - \hat{\sigma}_m\mathbf{I} = \boldsymbol{\sigma} - p\mathbf{I} - (\sigma_m - p)\mathbf{I} = \boldsymbol{\sigma} - \sigma_m\mathbf{I} = \mathbf{S}$$

Thus we have

$$F(\hat{\sigma}_{ij}) = F(S_{ij}, \sigma_m - p)$$

Deviatoric functions

$$F(S_{ij}) = f(S_{ij}) - \sigma_Y$$



Effect of pressure variation

$$\text{Let } \hat{\boldsymbol{\sigma}} = \boldsymbol{\sigma} - p\mathbf{I} \quad \Rightarrow \quad \hat{\sigma}_m = \sigma_m - p$$

Deviatoric stress

$$\hat{\mathbf{S}} = \hat{\boldsymbol{\sigma}} - \hat{\sigma}_m\mathbf{I} = \boldsymbol{\sigma} - p\mathbf{I} - (\sigma_m - p)\mathbf{I} = \boldsymbol{\sigma} - \sigma_m\mathbf{I} = \mathbf{S}$$

Thus we have

$$F(\hat{\sigma}_{ij}) = F(S_{ij}, \sigma_m - p)$$

Deviatoric functions

$$F(S_{ij}) = f(S_{ij}) - \sigma_Y$$

Example: Tresca's effective stress

$$\tau_e = \sigma_1 - \sigma_3 = S_1 + \sigma_m - (S_3 + \sigma_m) = S_1 - S_3$$



Mechanism of plastic slip





Mechanism of plastic slip



- Plastic strain is permanent.

$$\epsilon = \epsilon^p + \epsilon^e$$

is called additive decomposition.

Mechanism of plastic slip



- Plastic strain is permanent.

$$\epsilon = \epsilon^p + \epsilon^e$$

is called additive decomposition.

- Plastic flow preserves volume.

$$\epsilon_{11}^p + \epsilon_{22}^p + \epsilon_{33}^p = 0$$

therefore ϵ^p is a deviatoric tensor.

Mechanism of plastic slip



- Elastic constants E , ν are independent of plastic strain.

- Plastic strain is permanent.

$$\epsilon = \epsilon^p + \epsilon^e$$

is called additive decomposition.

- Plastic flow preserves volume.

$$\epsilon_{11}^p + \epsilon_{22}^p + \epsilon_{33}^p = 0$$

therefore ϵ^p is a deviatoric tensor.

Mechanism of plastic slip



- Plastic strain is permanent.

$$\epsilon = \epsilon^p + \epsilon^e$$

is called additive decomposition.

- Plastic flow preserves volume.

$$\epsilon_{11}^p + \epsilon_{22}^p + \epsilon_{33}^p = 0$$

therefore ϵ^p is a deviatoric tensor.

- Elastic constants E , ν are independent of plastic strain.
- Hydrostatic pressure acting alone does not cause yielding. It may, though, influence the magnitude of σ_Y .

Mechanism of plastic slip



- Plastic strain is permanent.

$$\epsilon = \epsilon^p + \epsilon^e$$

is called additive decomposition.

- Plastic flow preserves volume.

$$\epsilon_{11}^p + \epsilon_{22}^p + \epsilon_{33}^p = 0$$

therefore ϵ^p is a deviatoric tensor.

- Elastic constants E , ν are independent of plastic strain.
- Hydrostatic pressure acting alone does not cause yielding. It may, though, influence the magnitude of σ_Y .
- Metals are generally insensitive to p .

Mechanism of plastic slip



- Plastic strain is permanent.

$$\epsilon = \epsilon^p + \epsilon^e$$

is called additive decomposition.

- Plastic flow preserves volume.

$$\epsilon_{11}^p + \epsilon_{22}^p + \epsilon_{33}^p = 0$$

therefore ϵ^p is a deviatoric tensor.

- Elastic constants E , ν are independent of plastic strain.
- Hydrostatic pressure acting alone does not cause yielding. It may, though, influence the magnitude of σ_Y .
- Metals are generally insensitive to p .
- Slip stress may or might not be influenced by the normal force (not shown in figure).



Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.



Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.

2. Formulation

$$\|S\| \leq \text{const.}$$



Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.

2. Formulation

$$\|S\| \leq \text{const.}$$

3. Calibration: tensile test

$$S = \begin{bmatrix} \frac{2}{3}\sigma & 0 & 0 \\ 0 & -\frac{1}{3}\sigma & 0 \\ 0 & 0 & -\frac{1}{3}\sigma \end{bmatrix}$$



Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.

2. Formulation

$$\|\mathbf{S}\| \leq \text{const.}$$

3. Calibration: tensile test

$$\mathbf{S} = \begin{bmatrix} \frac{2}{3}\sigma & 0 & 0 \\ 0 & -\frac{1}{3}\sigma & 0 \\ 0 & 0 & -\frac{1}{3}\sigma \end{bmatrix}$$

$$\|\mathbf{S}\| = |\sigma| \sqrt{\frac{4}{9} + \frac{1}{9} + \frac{1}{9}} = \sqrt{\frac{2}{3}} |\sigma|$$



Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.

2. Formulation

$$\|\mathbf{S}\| \leq \text{const.}$$

3. Calibration: tensile test

$$\mathbf{S} = \begin{bmatrix} \frac{2}{3}\sigma & 0 & 0 \\ 0 & -\frac{1}{3}\sigma & 0 \\ 0 & 0 & -\frac{1}{3}\sigma \end{bmatrix}$$

$$\|\mathbf{S}\| = |\sigma| \sqrt{\frac{4}{9} + \frac{1}{9} + \frac{1}{9}} = \sqrt{\frac{2}{3}} |\sigma|$$

$$\|\mathbf{S}\| \leq \sqrt{\frac{2}{3}} \sigma_Y = \text{const.}$$

Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.

2. Formulation

$$\|\mathbf{S}\| \leq \text{const.}$$

3. Calibration: tensile test

$$\mathbf{S} = \begin{bmatrix} \frac{2}{3}\sigma & 0 & 0 \\ 0 & -\frac{1}{3}\sigma & 0 \\ 0 & 0 & -\frac{1}{3}\sigma \end{bmatrix}$$

$$\|\mathbf{S}\| = |\sigma| \sqrt{\frac{4}{9} + \frac{1}{9} + \frac{1}{9}} = \sqrt{\frac{2}{3}} |\sigma|$$

$$\|\mathbf{S}\| \leq \sqrt{\frac{2}{3}} \sigma_Y = \text{const.}$$

Effective stress

$$\sigma_e = \sqrt{\frac{3}{2}} \|\mathbf{S}\| \quad (\text{tension} = \text{compression})$$



Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.

2. Formulation

$$\|\mathbf{S}\| \leq \text{const.}$$

3. Calibration: tensile test

$$\mathbf{S} = \begin{bmatrix} \frac{2}{3}\sigma & 0 & 0 \\ 0 & -\frac{1}{3}\sigma & 0 \\ 0 & 0 & -\frac{1}{3}\sigma \end{bmatrix}$$

$$\|\mathbf{S}\| = |\sigma| \sqrt{\frac{4}{9} + \frac{1}{9} + \frac{1}{9}} = \sqrt{\frac{2}{3}} |\sigma|$$

$$\|\mathbf{S}\| \leq \sqrt{\frac{2}{3}} \sigma_Y = \text{const.}$$

Effective stress

$$\sigma_e = \sqrt{\frac{3}{2}} \|\mathbf{S}\| \quad (\text{tension} = \text{compression})$$

$$\sigma_e = \sqrt{3J_2} = \sqrt{\frac{3}{2}S_{ij}S_{ij}} = \text{HMH}$$



Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.

2. Formulation

$$\|\mathbf{S}\| \leq \text{const.}$$

3. Calibration: tensile test

$$\mathbf{S} = \begin{bmatrix} \frac{2}{3}\sigma & 0 & 0 \\ 0 & -\frac{1}{3}\sigma & 0 \\ 0 & 0 & -\frac{1}{3}\sigma \end{bmatrix}$$

$$\|\mathbf{S}\| = |\sigma| \sqrt{\frac{4}{9} + \frac{1}{9} + \frac{1}{9}} = \sqrt{\frac{2}{3}} |\sigma|$$

$$\|\mathbf{S}\| \leq \sqrt{\frac{2}{3}} \sigma_Y = \text{const.}$$

Effective stress

$$\sigma_e = \sqrt{\frac{3}{2}} \|\mathbf{S}\| \quad (\text{tension} = \text{compression})$$

$$\sigma_e = \sqrt{3J_2} = \sqrt{\frac{3}{2}S_{ij}S_{ij}} = \text{HMH}$$

4. Prediction: pure shear

$$\sigma_e = \sqrt{\frac{3}{2}(2\tau^2)} = \sqrt{3} |\tau| \leq \sigma_Y$$



Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.

2. Formulation

$$\|\mathbf{S}\| \leq \text{const.}$$

3. Calibration: tensile test

$$\mathbf{S} = \begin{bmatrix} \frac{2}{3}\sigma & 0 & 0 \\ 0 & -\frac{1}{3}\sigma & 0 \\ 0 & 0 & -\frac{1}{3}\sigma \end{bmatrix}$$

$$\|\mathbf{S}\| = |\sigma| \sqrt{\frac{4}{9} + \frac{1}{9} + \frac{1}{9}} = \sqrt{\frac{2}{3}} |\sigma|$$

$$\|\mathbf{S}\| \leq \sqrt{\frac{2}{3}} \sigma_Y = \text{const.}$$

Effective stress

$$\sigma_e = \sqrt{\frac{3}{2}} \|\mathbf{S}\| \quad (\text{tension} = \text{compression})$$

$$\sigma_e = \sqrt{3J_2} = \sqrt{\frac{3}{2}S_{ij}S_{ij}} = \text{HMH}$$

4. Prediction: pure shear

$$\sigma_e = \sqrt{\frac{3}{2}(2\tau^2)} = \sqrt{3} |\tau| \leq \sigma_Y$$

$$\tau_Y = \frac{\sigma_Y}{\sqrt{3}}$$



Von Mises' criterion (1913)

1. Hypothesis

Pressure independence.

2. Formulation

$$\|\mathbf{S}\| \leq \text{const.}$$

3. Calibration: tensile test

$$\mathbf{S} = \begin{bmatrix} \frac{2}{3}\sigma & 0 & 0 \\ 0 & -\frac{1}{3}\sigma & 0 \\ 0 & 0 & -\frac{1}{3}\sigma \end{bmatrix}$$

$$\|\mathbf{S}\| = |\sigma| \sqrt{\frac{4}{9} + \frac{1}{9} + \frac{1}{9}} = \sqrt{\frac{2}{3}} |\sigma|$$

$$\|\mathbf{S}\| \leq \sqrt{\frac{2}{3}} \sigma_Y = \text{const.}$$

Effective stress

$$\sigma_e = \sqrt{\frac{3}{2}} \|\mathbf{S}\| \quad (\text{tension} = \text{compression})$$

$$\sigma_e = \sqrt{3J_2} = \sqrt{\frac{3}{2}S_{ij}S_{ij}} = \text{HMH}$$

4. Prediction: pure shear

$$\sigma_e = \sqrt{\frac{3}{2}(2\tau^2)} = \sqrt{3} |\tau| \leq \sigma_Y$$

$$\tau_Y = \frac{\sigma_Y}{\sqrt{3}}$$

5. Validation (next lecture)



Hydrostatic modification

Including the mean stress

$$F(\sigma_{ij}) = f(S_{ij}) + \alpha\sigma_m - \sigma_Y$$

where α is the dilatancy parameter.



Hydrostatic modification

Including the mean stress

$$F(\sigma_{ij}) = f(S_{ij}) + \alpha\sigma_m - \sigma_Y$$

where α is the dilatancy parameter.

Examples:

- Tresca \Rightarrow Mohr-Coulomb
- von Mises \Rightarrow Drucker-Prager
- Hill \Rightarrow Caddell-Raghava-Atkins

In general, we keep the deviatoric and hydrostatic variables separated.



Hydrostatic modification

Including the mean stress

$$F(\sigma_{ij}) = f(S_{ij}) + \alpha\sigma_m - \sigma_Y$$

where α is the dilatancy parameter.

Examples:

- Tresca \Rightarrow Mohr-Coulomb
- von Mises \Rightarrow Drucker-Prager
- Hill \Rightarrow Caddell-Raghava-Atkins

In general, we keep the deviatoric and hydrostatic variables separated.

Note: The yield stress σ_Y is still a material constant (not variable).



Influence of normal stress (1/2)

Resolved shear stress: $\tau_S = \frac{A_0 \sigma}{A} \sin \phi$





Influence of normal stress (1/2)

Resolved shear stress: $\tau_S = \frac{A_0 \sigma}{A} \sin \phi = \sigma \cos \phi \sin \phi = \frac{\sigma}{2}$





Influence of normal stress (1/2)

Resolved shear stress: $\tau_S = \frac{A_0 \sigma}{A} \sin \phi = \sigma \cos \phi \sin \phi = \frac{\sigma}{2}$



tension



Influence of normal stress (1/2)

Resolved shear stress: $\tau_S = \frac{A_0 \sigma}{A} \sin \phi = \sigma \cos \phi \sin \phi = \frac{\sigma}{2}$



tension



compression



Influence of normal stress (1/2)

Resolved shear stress: $\tau_S = \frac{A_0 \sigma}{A} \sin \phi = \sigma \cos \phi \sin \phi = \frac{\sigma}{2}$



tension



compression



Conclusion: If normal stress plays no role, then $\sigma_{Yc} = \sigma_{Yt}$.



Influence of normal stress (2/2)

- We know that for Tresca and von Mises criteria $\sigma_{Yc} = \sigma_{Yt} = \sigma_Y$.



Influence of normal stress (2/2)

- We know that for Tresca and von Mises criteria $\sigma_{Yc} = \sigma_{Yt} = \sigma_Y$.
- Denote $\tau_{SY} = \sigma_Y/2$ the resolved shear stress at yield (acting in combination with normal stress).



Influence of normal stress (2/2)

- We know that for Tresca and von Mises criteria $\sigma_{Yc} = \sigma_{Yt} = \sigma_Y$.
- Denote $\tau_{SY} = \sigma_Y/2$ the resolved shear stress at yield (acting in combination with normal stress).
- Let τ_Y be the yield stress at shear (under pure shear conditions).



Influence of normal stress (2/2)

- We know that for Tresca and von Mises criteria $\sigma_{Yc} = \sigma_{Yt} = \sigma_Y$.
- Denote $\tau_{SY} = \sigma_Y/2$ the resolved shear stress at yield (acting in combination with normal stress).
- Let τ_Y be the yield stress at shear (under pure shear conditions).

Tresca

$$\tau_Y = \frac{\sigma_Y}{2} = \tau_{SY}$$

Influence of normal stress (2/2)

- We know that for Tresca and von Mises criteria $\sigma_{Yc} = \sigma_{Yt} = \sigma_Y$.
- Denote $\tau_{SY} = \sigma_Y/2$ the resolved shear stress at yield (acting in combination with normal stress).
- Let τ_Y be the yield stress at shear (under pure shear conditions).

Tresca

$$\tau_Y = \frac{\sigma_Y}{2} = \tau_{SY}$$

von Mises

$$\tau_Y = \frac{\sigma_Y}{\sqrt{3}} = \frac{2}{\sqrt{3}}\tau_{SY} > \tau_{SY}$$



Influence of normal stress (2/2)

- We know that for Tresca and von Mises criteria $\sigma_{Yc} = \sigma_{Yt} = \sigma_Y$.
- Denote $\tau_{SY} = \sigma_Y/2$ the resolved shear stress at yield (acting in combination with normal stress).
- Let τ_Y be the yield stress at shear (under pure shear conditions).

Tresca

$$\tau_Y = \frac{\sigma_Y}{2} = \tau_{SY}$$

von Mises

$$\tau_Y = \frac{\sigma_Y}{\sqrt{3}} = \frac{2}{\sqrt{3}}\tau_{SY} > \tau_{SY}$$

Conclusion: The presence of normal stress decreases τ_{SY} for von Mises' condition.